
Rolls

CANADA

FLOODED DEEP CYCLE BATTERY

12 FS GC-HC





Series	FS	Warranty	1 Year
Volts	12	BCI	GC12
Cells	6	Plates/Cell	11
Terminal Type		UTL	
Included Hardware		Stainless Steel K-Lock Nut	
Size & Threads		5/16"-18	

Charge

Charge Voltage Range	14.7-15 V/cell @ 25°C (77°F)
Recommended Charge Current	15 A
Maximum Charge Current	25 A
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	563
Marine Crank Amps (MCA) 32°F / 0°C	703
Reserve Capacity (RC @ 25A)	284 Minutes
Reserve Capacity (RC @ 75A)	79 Minutes

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	75%	50%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	**206 AH**	**2.06 A**
@ 72 Hour Rate	**195 AH**	**2.71 A**
@ 50 Hour Rate	**184 AH**	**3.69 A**
@ 20 Hour Rate	**155 AH**	**7.75 A**
@ 15 Hour Rate	**147 AH**	**9.82 A**
@ 10 Hour Rate	**136 AH**	**13.64 A**
@ 8 Hour Rate	**133 AH**	**16.66 A**
@ 5 Hour Rate	**122 AH**	**24.49 A**
@ 1 Hour Rate	**62 AH**	**62 A**

Amphere hour capacity ratings based on specific gravity of 1.280 at 25°C (77°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

Specifications


Certified System™
SAI GLOBAL
ISO 9001 Quality

Weight	37.5 kg	82.5 lbs
Length	33.3 cm	13.13"
Width	18.2 cm	7.17"
Height Inc. Term.	27.4 cm	10.8"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	38 mm	1.5"
Container	Polypropylene	
Cover	Polypropylene	
Handles	Top Molded Strap Brackets	


Cycle Life vs. Depth of Discharge



Voltage vs. Depth of Discharge

DISCHARGE	0%	25%	50%	75%	100%
20 HR AH RATE	2.10 V	2.07 V	2.00 V	1.92 V	1.75 V
10 HR AH RATE	2.10 V	2.06 V	1.98 V	1.89 V	1.75 V
3 HR AH RATE	2.10 V	2.03 V	1.95 V	1.86 V	1.75 V
1 HR AH RATE	2.10 V	2.01 V	1.93 V	1.84 V	1.75 V

Detailed Illustration



Rev.#2 | April 2021